



Harris
WolverineTM

Two Ram Baler

Processes:

Newspaper (ONP)
Cardboard (OCC)
High Grade Paper
Solid Waste (MSW)
Plastics (PET, HDPE, Film)
Cans (Steel/Aluminum)
Non-Ferrous Metals

The Harris WolverineTM is an affordable, durable, two ram baler with a small footprint perfect for operations that do not require high production volumes, but still require multi-product versatility.





Harris Wolverine™

Standard Features:

Hydraulic

- Highest baling force (88 tons, 80 tonne) and ram face pressure (145 psi, 10 bar) in it's class
- Flooded suction pump inlet
- Full regenerative hydraulic system
- 21 second dry cycle time

Structural

- Largest chargebox opening (42" x 60") (1067 mm x 1524 mm) in it's class
- Standard export bale size (31" x 46" x 61" avg) (787mm x 1168mm x 1549mm)
- Uni-body construction for superior strength and durability
- Clevis pin mount cylinders
- High quality replaceable floor liners, AR 500 Brinell hardness and segmented strips for easy replacement
- Serrated stationary shear knife
- Replaceable hold downs
- "EZ Out" oversize bale opening (without Combo Door option)

Operational

- State-of-the-art controls with an Operator Interface Terminal (OIT) displays continuous operating information and built-in diagnostic system with phone modem.
- Programmable controller with multiple material programs
- Automatic wire tier system
- Conveyor controls with adjustable photo eyes

Safety

- Wire tier and bale exit guards are hinged to facilitate easy access for maintenance and incorporates magnetic safety interlock switches for operational safety.
- Category 3 Safety System includes double redundant circuitry, safety interlocks and emergency stop devices.
- A safety monitoring relay continuously checks the status of the safety system.
- Hopper access door is provided with a double pole magnetic safety interlock switch and a dual trapped key interlock to prevent access when the baler is energized.

Benefits

- Affordable, durable, two-ram baler with a small footprint
- Perfect for operations that don't require high production volumes, but still require multi-product versatility, low labor cost, provided by the traditional two-ram baler with automatic strapping
- Laser ram positioning - reliable; simple to use and adjust, easy maintenance and setup
- Touch screen color display with function keys and programmable logic controller. Operating system is pre-programmed with multiple material selections and programmable settings. User friendly manual controls are provided for all functions.
- Backed by Harris and our network of authorized distributors.



Call today for more information

770-631-7290

800-373-9131

www.harrisequip.com

*All products and features are subject to change. Photos not necessarily representative of new equipment



Harris ©2010 - Wolverine10 -